BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images, please do not report the images to the Image Problem Mailbox.

PCT WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : A23C 3/00, A23L 3/00 — A2

(11) International Publication Number: **WO 98/07328**

(43) International Publication Date: 26 February 1998 (26.02.98)

(21) International Application Number: PCT/DK97/00589

(22) International Filing Date: 22 December 1997 (22.12.97)

(71) Applicant *(for all designated States except US)*: NIRO A/S [DK/DK]; Gladsaxevej 305, DK-2860 Søborg (DK).

(72) Inventors; and

(75) Inventors/Applicants *(for US only)*: SØRENSEN, Jens, Mourits [DK/DK]; Skovridergårdsvej 7, DK-2830 Virum (DK). RASMUSSEN, Carsten, Ole [DK/DK]; Magleholm 16, DK-2600 Glostrup (DK).

(74) Agents: SIMONSEN, Christian, Rosendal et al.; Internationalt Patent-Bureau, Høje Taastrup Boulevard 23, DK-2630 Taastrup (DK).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

Before the expiration of the time limit referred to in Article 21(2)(a) on the request of the applicant.
Without international search report and to be republished upon receipt of that report.
Without classification; title and abstract not checked by the International Searching Authority.

(54) Title: A METHOD OF IMPARTING AN ULTRA-SHORT, MOMENTANEOUS HEAT TREATMENT TO A LIQUID



(57) Abstract

In a method of providing a brief heat treatment to a liquid by mixing steam therein followed by flash cooling at reduced pressure, very short and easily adjustable holding time at elevated temperature is obtained by adjustable increase of the amount of steam injected into the liquid to amounts exceeding those which condense by contacting the liquid. The method is efficient for heat treatment, such as sterilization, of heat sensitive materials including food products of high viscosity.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	ES	Spain	LS	Lesotho	SI	Slovenia
AM	Armenia	FI	Finland	LT	Lithuania	SK	Slovakia
AT	Austria	FR	France	LU	Luxembourg	SN	Senegal
AU	Australia	GA	Gabon	LV	Latvia	SZ	Swaziland
AZ	Azerbaijan	GB	United Kingdom	MC	Monaco	TD	Chad
BA	Bosnia and Herzegovina	GE	Georgia	MD	Republic of Moldova	TG	Togo
BB	Barbados	GH	Ghana	MG	Madagascar	TJ	Tajikistan
BE	Belgium	GN	Guinea	MK	The former Yugoslav Republic of Macedonia	TM	Turkmenistan
BF	Burkina Faso	GR	Greece			TR	Turkey
BG	Bulgaria	HU	Hungary	ML	Mali	TT	Trinidad and Tobago
BJ	Benin	IE	Ireland	MN	Mongolia	UA	Ukraine
BR	Brazil	IL	Israel	MR	Mauritania	UG	Uganda
BY	Belarus	IS	Iceland	MW	Malawi	US	United States of America
CA	Canada	IT	Italy	MX	Mexico	UZ	Uzbekistan
CF	Central African Republic	JP	Japan	NE	Niger	VN	Viet Nam
CG	Congo	KE	Kenya	NL	Netherlands	YU	Yugoslavia
CH	Switzerland	KG	Kyrgyzstan	NO	Norway	ZW	Zimbabwe
CI	Côte d'Ivoire	KP	Democratic People's Republic of Korea	NZ	New Zealand		
CM	Cameroon			PL	Poland		
CN	China	KR	Republic of Korea	PT	Portugal		
CU	Cuba	KZ	Kazakstan	RO	Romania		
CZ	Czech Republic	LC	Saint Lucia	RU	Russian Federation		
DE	Germany	LI	Liechtenstein	SD	Sudan		
DK	Denmark	LK	Sri Lanka	SE	Sweden		
EE	Estonia	LR	Liberia	SG	Singapore		

A METHOD OF IMPARTING AN ULTRA-SHORT, MOMENTANEOUS HEAT TREATMENT TO A LIQUID

Field of the Invention

The present invention relates to heat treatment of heat sensitive liquids by steam injection. The heat treatment may have different purposes such as complete or partial sterilization or stabilization of liquid food products or pharmaceuticals, or stripping of volatile components from the liquid.

Background of the invention

When applying a heat treatment to heat sensitive materials it is often advantageous to apply a relatively high temperature for a short period in preference to using a more prolonged treatment at lower temperature. Thus, when the desired beneficial effect of the heat treatment, for instance destruction of microorganisms and their germs, is enhanced to a greater extent by raise of temperature than the heat damage is increased by such a raise, it can be advantageous to perform the heat treatment at relatively high temperature avoiding an increased heat damage by substantially shortening the time period in which the material is at elevated temperature.

This principle is utilized i.a. in the socalled UHT processing of milk with a view of obtaining a long shelf-life at ambient temperature.

For a more detailed explanation of prior art technology within this field reference is made to H. Burton: Ultra-High-Temperature Processing of Milk and Milk Products (Elsevier Applied Science Publishers

Ltd., 1988). Also Ullmann's Encyclopedia, 5th ed. (1988), Vol. A 11, pages 549-552, discusses UHT sterilizing of milk and explains how various combinations of heating time and temperature influence microbial spores destruction, vitamin destruction, enzyme deactivation, protein denaturation and color changes.

In UHT processes the increase of temperature is achieved by using indirect heaters or direct heaters in which steam is contacted with and condenses into the liquid to be treated.

When exploiting the present invention, only direct steam heating comes into consideration as heating system, because a very rapid temperature increase is crucial as evident from the below description of the invention. Besides, the indirect heating principle is less suitable for liquids of high viscosity.

Typically UHT processing of milk comprises a heating step in which the milk is contacted with steam, followed by passage through a retention or holding zone to a flash cooling step wherein a momentaneous evaporative cooling takes place.

In the heating step direct contact between the liquid and steam takes place in a mixing zone.

From the mixing zone the liquid passes through a holding zone decisive for the duration of the heat treatment and which is important for a uniform treatment of all parts of the liquid.

In the literature referred to above as well as in Encyclopedia of Food Science, Food Technology and Nutrition, pages 2305-2313, 1993, it is emphasized that the holding zone at all times during operation must be completely filled with liquid. This means that the amount of steam introduced in the mixing zone must not exceed the amount which condenses therein.

From the holding zone the liquid passes through a

restricting means creating a substantial pressure drop, and the liquid reaches a chamber of lower pressure wherein a momentaneous evaporation takes place, whereby the liquid is cooled to a temperature at which it is not subjected to any heat damage.

The vapours formed by this evaporation are withdrawn to a condenser, usually supplied with heat-regeneration means, and the non-evaporated part of the liquid is recovered from the bottom portion of the chamber as a marketable product or as an intermediate for further processing.

It is important that a vigorous mixing of steam into the liquid takes place in the mixing zone, especially when the liquid to be treated is of high viscosity, such as concentrates of milk and other food products. Equipment suitable for this purpose is described in Applicant's published International Patent Applications WO 94/13395 and WO 96/22830, incorporated herein by reference.

The apparatus described in said two International Patent Applications is of the type having a disc-shaped rotor in a housing into which the steam injection is carried out in a limited zone above the rotor at a distance from both the circumference and the centre of the rotor. This type of apparatuses enables very fast heating of even high-viscosity liquids, within the dairy industry it is known as a Niro LSI™ apparatus.

It is a drawback of the above described prior art processes that the minimum time period, in which the liquid is at maximum temperature cannot be reduced as much as desired. In the period necesssary for the liquid to pass through the holding zone, the liquid is near or at the maximum temperature. Passage through such a zone having a certain volume has hitherto usually been regarded as important for obtaining the

desired results. Moreover, constructional features restrict the possibilities of decreasing said volume. Further, processing conditions such as the acceptable pressures and thus temperatures set limits as to the velocity at which the liquid can be forced through the holding zone when the processing is performed as described above.

Summary of the Invention

It is an object of the invention to provide a method for heat treatment of a liquid by direct steam heating, by which method it is possible to adjustably reduce the time period in which the liquid is at maximum temperature and at the same time obtain an efficient heat treatment of all parts of the liquid.

We have now found that the above object and other advantages may be obtained by mixing an amount of steam into the liquid in the mixing zone greater than the amount which condenses in the heating step. Thereby the non-condensed steam will partly displace the liquid from the holding zone and decrease the residence time thereof in said zone. Surprisingly this decrease of residence time can be obtained without impairing the function of the holding zone as a means for securing an efficient heat treatment.

Consequently, the invention deals with a method of imparting an ultra-short, momentaneous heat treatment to a liquid by mixing steam into a stream of said liquid in a mixing zone, passing the stream of liquid through a holding zone and, after passage of a pressure controlling restricting means, subsequently into a flash cooler, which method is characterized in that the amount of steam mixed into the stream of liquid, is larger than the one which condenses by contacting the

liquid, whereby the non-condensed portion of the steam serves to obtain passage of the liquid through the holding zone with reduced residence time therein compared with the residence time obtained in the same holding zone if only the amount of steam that condenses by contacting the liquid had been used.

The method is not restricted to the use of any specific apparatus for forming the mixing zone, but it is essential that a quick and efficient mixing of the liquid and the steam is obtained using only a very short residence time for the liquid in the zone.

As an example of an apparatus suitable for creating the mixing zone is the Niro LSI™ apparatus described above. Obviously a prolonged residence time in the mixing zone after contact with steam has started would prevent obtainment of the above specified object of the invention.

The holding zone may encompass a separate unit or vessel, but it may also be a part of the same apparatus which creates the mixing zone and/or be formed in pipes and other equipment connecting the mixing zone with the restricting means.

As restricting means an adjustable valve may suitably be used which enables maintenance of a pressure in the mixing zone and the holding zone corresponding to the maximum temperature desired in the liquid. In case a non-adjustable restricting means such as an orifice plate is used said pressure can of course be obtained by adjusting the amounts of steam and liquid introduced into the mixing zone.

Downstream of the restricting means the pressure is sufficiently low, below or above atmospheric pressure, to ensure a flash cooling of the liquid by evaporation. The surplus of steam, which reaches the flash cooling step, is withdrawn to the condenser

together with the vapour created by the momentaneous evaporation of part of the heated liquid.

By the process according to the invention it is possible to reduce the residence time for the liquid at the maximum temperature to less than 1/100 of what has been possible with the prior art direct steam heating processes where all steam is condensed before leaving the mixing zone.

Brief Description of the Drawing

The sole Figure on the drawing diagrammatically shows a flow-chart of an embodiment of the method according to the invention.

Detailed Description of Preferred Embodiments

On the drawing a mixing zone is represented by 1. This may typically be formed by a Niro LSI™ apparatus or other equipment enabling a similar fast mixing of steam and liquid. The liquid to be treated is fed to the mixing zone through a conduit 2 and steam is provided through conduit 3. The steam is introduced in an amount corresponding to the maximum temperature at which it is desired to heat the liquid, adjusted to compensate heat loss in the equipment. The steam may be superheated, but typically its temperature is only little above the saturation temperature or at the saturation temperature.

It is an essential feature of the method according to the invention that the amount of steam introduced through 3 is in excess of the minimum amount required to obtain the desired heating, that means the amount of steam introduced is higher than the amount which condenses by contacting the liquid.

In the embodiment depicted the liquid after being heated and diluted by the water created by steam condensation therein passes into a pipe 4 which, together with the exit part of the equipment forming the mixing zone 1 constitutes a holding or retention zone. Also the non-condensed portion of the steam introduced through 3 passes from the mixing zone into the holding zone in pipe 4.

The liquid as well as the surplus of steam leaves the pipe 4 through a valve 5. In a preferred embodiment this valve may be adjusted to provide a back pressure suitable for maintaining the desired conditions in 1 and 4.

That part of the steam, which is not condensed, as well as the heated liquid pass from valve 5 into a flash cooler 6 where a pressure substantially below the one residing in the holding zone in pipe 4 causes a momentaneous evaporation, whereby that part of the liquid which does not evaporate is cooled to a temperature typically not far from the temperature at which the liquid were introduced through conduit 2.

The vapour formed by this evaporation together with the non-condensed steam introduced through 5 is withdrawn through a duct 7 to a condenser (not shown) for pressure control.

The liquid cooled by the evaporation collects in the bottom portion 8 of the flash cooler from where it is recovered, suitably by means of a pump 9.

Adjustment according to the invention of the amount of steam led to the system through conduit 3 forms a very convenient and efficient way of adjusting the total residence time of the liquid at elevated temperature. By increasing said amount sufficiently it is possible to reduce the time period from the liquid contactes the steam in 1 to the liquid passes valve 5

for flash cooling to only a small fraction of the corresponding time period if no surplus of steam were used.

When it is desired to heat the liquid at a temperature above 100°C, for example when sterilizing milk products at approximately 150°C in 1/100 sec., the pressure in 1 and 4 will be over-atmospheric.

If on the other hand the maximum temperature is below 100°C an under-atmospheric pressure exists in the mixing zone and the holding zone.

In the following important fields of application are summarized.

Especially when the mixing zone has moving, agitating mechanical means to ensure a rapid and efficient dispersion of the steam into the liquid, as is the case f.inst. by the Niro LSI™ apparatus, the liquid to be treated can be a high viscous food product, preferably concentrate of milk or of a milk fraction or a fractionated or whole egg product, which is subjected to the heat treatment with a view of reducing the contents of microorganisms or microorganisms spores.

Typically such heat treatment may preceed a spray drying or other processing of the liquid food product.

The liquid can f.inst. be a concentrate of baby-food or of milk or milk fractions with or without addition of other components such as sugar, such products having a dry solids content of 40-75% by weight and the steam temperature is then above 110°C, preferably 120-160°C and the amount of steam is adjusted to obtain a residence time for the liquid at that temperature of 0.5 sec. or less, preferably 0.01-0.2 sec.

By such a treatment the amount of germs of *Bacillus cereus* can be reduced from 10^6/ml to below 100/ml

without heat damage of the product. This means that the taste is not impaired in any substantial way, and the Solubility Index (SI) is not unacceptably increased. For instance for the heat treatment of a whole milk concentrate the SI can be kept below 0.2 ml, typically below 0.1 ml. The SI is measured at a dry solids contents of 13% by weight according to ADMI.

In the present specification and the attached claims the term milk is intended to cover whole milk as well as skim milk.

When treating a liquid comprising egg yolk or egg white or both, the maximum temperature is preferably only 65-70°C for a period less than 0.5 sec., preferably of 0.01-0.2 sec. to avoid coagulation of the product. However, with suitable additives it is possible to use higher temperatures.

Examples of other products suitable for being treated by the method according to the invention, either as such or as concentrates, are coffee whiteners, fruit juices, sweetened condensed milk and icecream mixes.

The method may be used for liquids in the shape of solutions, emulsions, dispersions, suspensions og slurries, for instance within the food and drink industry or the pharmaceutical and cosmetical industry.

The method may also find application when the liquid to be treated contains a compound more volatile than the other components thereof, in which case the treatment involves a removal of a substantial part of the volatile component by stripping thereof. Thus the method may be used to reduce the contents of alcohol in a fermented brewerage while maintaining an acceptable taste and flavour thereof.

In the following the method according to the invention is further illustrated by means of comparison

and embodiment examples.

Comparison Example

This comparison Example as well as the embodiment Examples 1 and 2 below were performed in a plant corresponding to the one described above in connection with the drawing. For mixing the liquid to be treated and the steam a Niro LSI ™ apparatus was used. A sensor was inserted in the holding zone to measure the maximum temperature achieved by the liquid being treated.

The comparison comprised two runs. The starting material for both was a whole milk concentrate having a dry solids contents of 47% by weight and at an initial temperature of 65°C.

The amount of steam led to the mixing zone corresponded to the one which, based on theoretical calculations (including heat loss to the equipment), would condense completely when heating the liquid to the below specified temperatures.

Before the heat treatment spores of *Bacillus cereus* were added to the milk concentrate to obtain a concentration of such spores of 2.7×10^6/ml.

After the treatment the concentrate was cooled to 65°C in the evaporative cooler, and the concentration of remaining spores of *Bacillus cereus* was measured. Said concentration is indicated below as CFU/ml, meaning "Colony Forming Units per ml".

In these runs where the holding zone was completely filled with liquid, an approximate residence time for said liquid in the holding zone can be calculated to 1 sec.

Details from these two runs appear from the below Table:

	Run 1	Run 2
Concentrate flow, l/h	132	128
Steam flow, kg/h	14	16
Steam pressure, bar	3.7	3.7
Steam temperature, °C	141	141
Maximum liquid temperature, °C	110	120
Spore concentration after the heat treatment, CFU/ml	9.0×10^3	$<1.0 \times 10^2$*

* The method used to determine the spore concentration comprised dilution of the concentrate necessitated by the high viscosity thereof. This dilution implied that the minimum spore concentration to be recorded as the result of this determination method is $<1.0 \times 10^2$, even if no colony forming units were found.

By visual and organoleptic evaluation of the treated product this was found acceptable, but determination of the solubility index according to ADMI, measured at a dry solids contents of 13% by weight, revealed that the product treated at a maximum temperature of 120°C had a SI of 0.4. Preferably, this index should be below 0.2.

Example 1

This Example was carried out using the same equipment as used in the above Comparison Example.

A whole milk concentrate having a dry solids contents of 47% by weight was heat treated from an initial temperature of 65°C to the various maximum temperatures indicated in the below Table. As it also appears from said Table when compared with the above Comparison Example, steam was used in an amount substantially exceeding the amount corresponding to

complete condensation.

Before the heat treatment spores of *Bacillus cereus* were added to obtain a total concentration thereof of 1.2×10^6 CFU/ml.

After the treatment the concentrate was cooled to 65°C in conventional manner in the evaporative cooler.

The various parameters as well as the concentration of spores after the treatment were as follows:

	Run 1	Run 2	Run 3	Run 4	Run 5
Concentrate flow, l/h	123	131	125	122	133
Steam flow, kg/h	22	25	27	29	33
Steam pressure, bar	2.0	2.2	2.4	2.6	3.0
Steam temperature, °C	120	123	125	129	133
Maximum liquid temperature, °C	118	121	123	127	131
Spore concentration after the heat treatment, CFU/ml	2.0×10^5	8.5×10^3	7.2×10^2	2.0×10^2	$<1.0 \times 10^2$

As explained in the Comparison Example above the result of the spore concentration analysis indicated as $<1.0 \times 10^2$ reflects the fact that actually no colony forming spores were revealed by propagation.

The treated milk concentrates did not show any kind of burning, discolouration or destruction of other functional properties. The solubility index after heat treatment at 131°C was 0.1. when determined by using the same method as in the above Comparison Example.

Example 2

Also in this Example the material to be treated was a whole milk concentrate having a dry solids contents of 47% by weight and at an initial temperature of 65°C. The same equipment was used as in the above Comparison Example and in Example 1.

Before treatment spores of *Bacillus stearothermo-*

philus were added to obtain a concentration thereof of $1.4x10^4$/ml. After the treatment the concentrate was cooled to 65°C in the evaporative cooler.

The various parameters of the method and the spore concentrations after the heat treatment appear from the following Table:

	Run 1	Run 2
Concentrate flow, l/h	142	140
Steam flow, kg/h	37	45
Steam pressure, bar	4.3	5.2
Steam temperature, °C	147	153
Maximum liquid temperature, °C	146	152
Spore concentration after the heat treatment, CFU/ml	$7.4x10^3$	$<1.0x10^2$

It is remarkable that even when the test organism, the very heat stable *Bacillus stearothermophilus*, is used as test organism, a substantially complete spore destruction is obtained in Run 2. This result was obtained without any kind of burning, discolouration or other destruction of functional properties, and the solubility index after the heat treatment at 152°C (measured as above) was only 0.1. This surprising result is due to the fact that the surplus of steam used in this Example is substantially above the amount which condensates by contact with the concentrate in the mixing zone. This will be evident by comparing the various parameters with those of the above Comparison Example.

PATENT CLAIMS

1. A method of imparting an ultra-short momentaneous heat treatment to a liquid by mixing steam into a stream of said liquid in a mixing zone, passing the stream of liquid through a holding zone and after passage of a pressure controlling restricting means subsequently into a flash cooler, characterized in that the amount of steam mixed into the stream of liquid is larger than the one which condenses by contacting the liquid, whereby the non-condensed portion of the steam serves to obtain passage of the liquid through the holding zone with reduced residence time therein compared with the residence time obtained in the same holding zone if only the amount of steam that condenses by contacting the liquid had been used.

2. A method according to claim 1, characterized in that the mixing zone has moving, agitating mechanical means to ensure a rapid and efficient dispersion of the steam into the liquid.

3. A method according to claim 1 or 2, characterized in that the liquid is a viscous food product, preferably a concentrate of milk or milk fractions with or without addition of other components such as sugar, or a fractionated or whole egg product, which is subjected to the heat treatment with a view of reducing the contents of microorganisms or microorganism spores.

4. A method according to claim 1 or 2, characterized in that the liquid is fresh milk for consumption.

5. A method according to claim 3 in which the liquid is a concentrate of baby food or milk or a milk product, with or without addition of other components such as sugar, such products having a dry solids contents of 40-75% by weight, and wherein the tempera-

ture of the steam is above 110°C, preferably 120-160°C, and the amount of steam is adjusted to obtain a residence time for the liquid at that temperature of 0.5 sec. or less.

6. A method according to claim 1 or 2, wherein the liquid is a non-dairy food product.

7. A method according to claim 3 wherein a liquid comprising egg yolk or egg white or both is heated at 65-70°C for a period less than 0.5 sec.

8. A method according to claim 1 or 2 wherein the heat treatment is performed on a liquid containing a component more volatile than the other components thereof and the treatment is made to remove a substantial part of said volatile component by stripping thereof.

9. A method according to claim 8 wherein the liquid is a fermented brewerage from which a content of alcohol is reduced by stripping during the treatment.


7
4
3
6
5
2
8
1
9

PCT D INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : A23C 3/037 — A3

(11) International Publication Number: **WO 98/07328**

(43) International Publication Date: 26 February 1998 (26.02.98)

(21) International Application Number: PCT/DK97/00589

(22) International Filing Date: 22 December 1997 (22.12.97)

(71) Applicant *(for all designated States except US)*: NIRO A/S [DK/DK]; Gladsaxevej 305, DK-2860 Søborg (DK).

(72) Inventors; and

(75) Inventors/Applicants *(for US only)*: SØRENSEN, Jens, Mourits [DK/DK]; Skovridergårdsvej 7, DK-2830 Virum (DK). RASMUSSEN, Carsten, Ole [DK/DK]; Magleholm 16, DK-2600 Glostrup (DK).

(74) Agents: SIMONSEN, Christian, Rosendal et al.; Internationalt Patent-Bureau, Høje Taastrup Boulevard 23, DK-2630 Taastrup (DK).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, GM, GW, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, US, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).

Published

With international search report.

Before the expiration of the time limit referred to in Article 21(2)(a) on the request of the applicant.

(88) Date of publication of the international search report:
15 October 1998 (15.10.98)

(54) Title: A METHOD OF IMPARTING AN ULTRA-SHORT, MOMENTANEOUS HEAT TREATMENT TO A LIQUID



(57) Abstract

In a method of providing a brief heat treatment to a liquid (2) by mixing steam (3) therein followed by flash cooling step (6) at reduced pressure with very short and easily adjustable holding time at elevated temperature is obtained by adjustable increase of the amount of steam injected into the liquid to amounts exceeding those which condense by contracting the liquid. The method is efficient for heat treatment, such as sterilization, of heat sensitive materials including food products of high viscosity.

FOR THE PURPOSES OF INFORMATION ONLY

Codes used to identify States party to the PCT on the front pages of pamphlets publishing international applications under the PCT.

AL	Albania	**ES**	Spain	**LS**	Lesotho	**SI**	Slovenia
AM	Armenia	**FI**	Finland	**LT**	Lithuania	**SK**	Slovakia
AT	Austria	**FR**	France	**LU**	Luxembourg	**SN**	Senegal
AU	Australia	**GA**	Gabon	**LV**	Latvia	**SZ**	Swaziland
AZ	Azerbaijan	**GB**	United Kingdom	**MC**	Monaco	**TD**	Chad
BA	Bosnia and Herzegovina	**GE**	Georgia	**MD**	Republic of Moldova	**TG**	Togo
BB	Barbados	**GH**	Ghana	**MG**	Madagascar	**TJ**	Tajikistan
BE	Belgium	**GN**	Guinea	**MK**	The former Yugoslav Republic of Macedonia	**TM**	Turkmenistan
BF	Burkina Faso	**GR**	Greece			**TR**	Turkey
BG	Bulgaria	**HU**	Hungary	**ML**	Mali	**TT**	Trinidad and Tobago
BJ	Benin	**IE**	Ireland	**MN**	Mongolia	**UA**	Ukraine
BR	Brazil	**IL**	Israel	**MR**	Mauritania	**UG**	Uganda
BY	Belarus	**IS**	Iceland	**MW**	Malawi	**US**	United States of America
CA	Canada	**IT**	Italy	**MX**	Mexico	**UZ**	Uzbekistan
CF	Central African Republic	**JP**	Japan	**NE**	Niger	**VN**	Viet Nam
CG	Congo	**KE**	Kenya	**NL**	Netherlands	**YU**	Yugoslavia
CH	Switzerland	**KG**	Kyrgyzstan	**NO**	Norway	**ZW**	Zimbabwe
CI	Côte d'Ivoire	**KP**	Democratic People's Republic of Korea	**NZ**	New Zealand		
CM	Cameroon			**PL**	Poland		
CN	China	**KR**	Republic of Korea	**PT**	Portugal		
CU	Cuba	**KZ**	Kazakstan	**RO**	Romania		
CZ	Czech Republic	**LC**	Saint Lucia	**RU**	Russian Federation		
DE	Germany	**LI**	Liechtenstein	**SD**	Sudan		
DK	Denmark	**LK**	Sri Lanka	**SE**	Sweden		
EE	Estonia	**LR**	Liberia	**SG**	Singapore		

INTERNATIONAL SEARCH REPORT

national application No
PCT/D[redacted]7/00589

A. CLASSIFICATION OF SUBJECT MATTER
IPC 6 A23C3/037

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)
IPC 6 A23C

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	GB 818 003 A (E. WILLOUGHBY ROLLINSON) 12 August 1959 see column 1, line 42 - line 52; claims 1,3,5,6; examples 7-10,20,21 see column 2, line 20 - line 29	1-3,5,7
A	US 4 605 444 A (WERNER & PFLEIDERER) 12 August 1986 see column 1, line 67 - column 2, line 56; claims 1,5	1,2,5
A	US 3 113 872 A (E. J. PERRY ET AL.) 10 December 1963 see the whole document	1,3,6-8
X	US 4 877 625 A (VALMONT) 31 October 1989 see the whole document	1,3,5,7

-/--

[X] Further documents are listed in the continuation of box C.

[X] Patent family members are listed in annex.

Special categories of cited documents :

"A" document defining the general state of the art which is not considered to be of particular relevance

"E" earlier document but published on or after the international filing date

"L" document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)

"O" document referring to an oral disclosure, use, exhibition or other means

"P" document published prior to the international filing date but later than the priority date claimed

"T" later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

"X" document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

"Y" document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

"&" document member of the same patent family

Date of the actual completion of the international search	Date of mailing of the international search report
16 July 1998	29/07/1998

Name and mailing address of the ISA	Authorized officer
European Patent Office, P.B. 5818 Patentlaan 2 NL - 2280 HV Rijswijk Tel. (+31-70) 340-2040, Tx. 31 651 epo nl. Fax: (+31-70) 340-3016	Guyon, R

Form PCT/ISA/210 (second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

nati	plication No
PCT/	/00589

C.(Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT

Category	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	H. BURTON: "ultra-high-temperature prcessing of milk and milk products" 1988 . ELSEVIER APPLIED SCIENCE . LONDON AND NEW YORK XP002071864 637	1-4,8
Y	see page 101, line 38 - page 102, line 3; figures 4.12,4.14A	6,7
Y	see figure 14.16 see page 109, line 31 - page 110, line 4	9
Y	US 5 105 724 A (R. KENNETH ET AL.) 21 April 1992 see column 6, line 64 - column 7, line 45; claims; figure 1	6,7
Y	US 4 009 286 A (GROUPEMENT D'INTERET ECONOMIQUE) 22 February 1977 see the whole document	9
A	US 3 666 497 A (ALLIED CHEM. CORP.) 30 May 1972 see the whole document	1
A	NL 7 709 303 A (STORK) 27 February 1979 see the whole document	1
A	EP 0 617 897 A (TETRA LAVAL) 5 October 1994 see the whole document	1
A	DATABASE WPI Week 8411 Derwent Publications Ltd., London, GB; Page 3, AN 84-067371 XP002071865 & SU 1 017 270 A (D. KANDELAKI ET AL.) , 15 May 1983 see abstract	6

Form PCT/ISA/210 (continuation of second sheet) (July 1992)

INTERNATIONAL SEARCH REPORT

[redacted] Application No
PCT/D[redacted]/00589

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
GB 818003	A		NONE		
US 4605444	A	12-08-1986	DE	3340116 A	23-05-1985
			FR	2554322 A	10-05-1985
			GB	2148902 A,B	05-06-1985
			NL	8403102 A,B,	03-06-1985
US 3113872	A	10-12-1963	NONE		
US 4877625	A	31-10-1989	FR	2609601 A	22-07-1988
			EP	0281431 A	07-09-1988
US 5105724	A	21-04-1992	US	5019407 A	28-05-1991
			AU	642233 B	14-10-1993
			AU	7466791 A	21-08-1991
			CA	2073867 A,C	24-07-1991
			EP	0540523 A	12-05-1993
			JP	5503853 T	24-06-1993
			WO	9111107 A	08-08-1991
US 4009286	A	22-02-1977	FR	2248319 A	16-05-1975
			AU	7147474 A	22-01-1976
			BE	816481 A	16-10-1974
			CA	1028261 A	21-03-1978
			DE	2429574 A	23-01-1975
			DK	328474 A,B,	17-03-1975
			GB	1472578 A	04-05-1977
			JP	1093087 C	16-04-1982
			JP	50046896 A	25-04-1975
			JP	56034273 B	08-08-1981
			LU	70359 A	28-11-1974
			NL	7408271 A	24-12-1974
US 3666497	A	30-05-1972	NONE		
NL 7709303	A	27-02-1979	NONE		
EP 617897	A	05-10-1994	AT	147235 T	15-01-1997
			AU	675287 B	30-01-1997
			AU	5908194 A	06-10-1994

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No
PCT/D[redacted]/00589

Patent document cited in search report	Publication date	Patent family member(s)	Publication date
EP 617897 A		BR 9401289 A	01-11-1994
		CA 2119612 A	30-09-1994
		CN 1105192 A	19-07-1995
		DE 69401372 D	20-02-1997
		DE 69401372 T	30-04-1997
		DK 617897 T	30-06-1997
		FI 941438 A	30-09-1994
		HU 66397 A	28-11-1994
		JP 6303899 A	01-11-1994
		NO 941143 A	30-09-1994
		PL 173849 B	29-05-1998
		RU 2088123 C	27-08-1997
		SE 9301027 A	30-09-1994
		US 5443857 A	22-08-1995
		ZA 9402005 A	05-04-1995